



Performance

Supported standard	ISO15693
Recommended operating frequency	13.56MHz
Memory(user programmable)	2k bits organized in 64 × 32 bits blocks
Maximum transmission speed	26.5kbits/sec.
Anticollision	Correspondence
Typical programming cycles(at +25)	100,000
Communication distance(at 25)	60 ~ 120cm *1
Magnetic field intensity of operation(at +25)	more than 100dB μ A/m(peliminary value)
Recommendation operation temperature	0 ~ +40
Recommendation storage temperature	-10 ~ 70
Protection structure	IP50(Supported standard IEC60529)
Vibration-proof nature	A sine wave ; 0 ~ 500MHz logarithms ; for each axial 9 minutes Acceleration ; more than 10G
Case quality of the material	General-purpose plastic
Weight	53g

Notes

- A presentation sample asks you for return.
- Demolition of a presentation sample asks you for reserve.
- Please keep a secret for the product under development.

The order and the reference about this product
THE FURUKAWA ELECTRIC CO., LTD.

Sales & Marketing Division Telecommunication Wireless Marketing department
 2-6-1, Marunouchi, Chiyoda-ku, Tokyo (〒100-8322)JAPAN
 TEL 03 - 3286 - 3414

In our journal, the representation characteristic value of this product is mainly carried. Since notes on use etc. have not carried, please give them to me about contents required in the case of use so that you may consult beforehand.

We can.